

Easywrap

Product Information Sheet

Issue: 01 Date: 05.04.13

DESCRIPTION Extruded polypropylene coiled tube which protects and helps establish trees

APPLICATION For the protection of trees against animal browsing, herbicide spray

SECTORS Forestry and Horticulture

Twin wall; best strength to weight ratio



Overlap: expands as tree grows

UV stabilised: provides minimum 5 year protection



Translucent green; maximises light transmission for photosynthesis

		TUBEX Easywrap		
Dimensions				
Height	m	0.2	0.6	0.75
Diameter	mm	50	50	50
Overlap tolerance	mm	32 (min) - 50 (max)	32 (min) - 50 (max)	32 (min) - 50 (max)
Av. Weight per tube	g	21.5	43.5	54
Packaging		For all sizes		
Nest		2	2	2
Bundle		100	150	150
Bag or strap banded		Bag	Bag	Bag

Material	For all sizes
Tube	Polypropylene
Colour	Green
Service Life	Minimum 3 years
Degradability	Photodegradable
Manufacturing tolerance	- 10mm
Recommended support	Cane

As part of its continual improvement process Fiberweb Geosynthetics Ltd reserve the right to change the properties listed on this data sheet without prior notice.

TM indicates a trade mark of Fiberweb plc or a Fiberweb Group company, many of which are registered in a number of countries around the world.