

Standard Vine Range

T: +44 (0)1621 874201
F: +44 (0)1621 874299

Product Information Sheet

Issue: 01 Date: 05.04.13

DESCRIPTION Extruded polypropylene tube which protects and helps establish vines

APPLICATION For the protection of vines against animal browsing, herbicide spray and for the improvement of growth through a microclimate

SECTORS Horticulture

Strengthening rods; prevents shelter tearing at stake area



Twin wall; best strength to weight ratio



UV stabilised: provides minimum 5 year protection



Flared rim; minimises stem abrasion



Laserline; shelter splits avoiding strangulation as tree grows



Pre-fitted releasable ties; quick, easy installation and maintenance



Translucent green; maximises light transmission for photosynthesis

		TUBEX Standard Vine Range	
Dimensions			
Height	m	0.4	0.5
Diameter	mm	73–105	73–105
No of ties		1	1
Type of tie		Releasable	Releasable
Size of tie	inch	9	9
Top tie height (+ tolerance)	mm	180–215	285–315
Av. Weight per tube	g	47.5	60
Packaging			
Nest		5	5
Bundle		60	60
Bag or strap banded		Bag	Bag

Material	For all sizes
Tube	Polypropylene
Tie	Nylon
Colour	Green
Service Life	Minimum 5 years
Degradability	Photodegradable
Manufacturing tolerance	- 10mm
Recommended support	Stake

*If you require other sizes that are not specified within this data sheet please get in contact.

As part of its continual improvement process Fiberweb Geosynthetics Ltd reserve the right to change the properties listed on this data sheet without prior notice.

TM indicates a trade mark of Fiberweb plc or a Fiberweb Group company, many of which are registered in a number of countries around the world.