

## Treeguard Range

T: +44 (0)1621 874201  
F: +44 (0)1621 874299

### Product Information Sheet

Issue: 01 Date: 05.04.13

**DESCRIPTION** Extruded and welded recycled HDPE mesh guard which protects and helps establish trees

**APPLICATION** For the protection of trees against animal browsing, herbicide spray

**SECTORS** Forestry and Horticulture

Weld line: shelter splits  
avoiding strangulation as  
plant grows



UV stabilised: provides  
minimum 5 year protection



Flared rim; minimises stem  
abrasion



Pre-fitted releasable ties;  
quick, easy installation and  
maintenance

		TUBEX Treeguard Range						
<b>Dimensions</b>								
Height	m	0.45	0.6	0.75	0.9	1.2	1.5	1.8
Diameter	mm	80–110	80–110	80–110	80–110	80–110	80–110	80–110
No of ties		1	1	2	2	2	2	2
Type of tie		Releasable	Releasable	Releasable	Releasable	Releasable	Releasable	Releasable
Size of tie	inch	10	10	10	10	10	10	10
Top tie height (+ tolerance)	mm	250	350	500	650	850	1090	1450
Bottom tie height (+ tolerance)	mm	-	-	250	250	250	250	250
Av. Weight per tube	g	77	103	129	154	206	257	309
Mesh aperture	mm	12	12	12	12	12	12	12
<b>Packaging</b>		For all sizes						
Nest		4				4		
Bundle		100				60		
Bag or strap banded		Bag				Bag		

<b>Material</b>	<b>For all sizes</b>
Tube	Recycled HDPE
Tie	Nylon
<b>Colour options</b>	Dark Green / Brown
<b>Service Life</b>	Minimum 5 years
<b>Degradability</b>	Photodegradable
<b>Manufacturing tolerance</b>	- /+ 15 (2 squares of mesh)
<b>Recommended support</b>	Stake

\*If you require other sizes that are not specified within this data sheet please get in contact.

As part of its continual improvement process Fiberweb Geosynthetics Ltd reserve the right to change the properties listed on this data sheet without prior notice.

TM indicates a trade mark of Fiberweb plc or a Fiberweb Group company, many of which are registered in a number of countries around the world.