

# Installation Guidance

## Shelterguard™ and Treeguard™

### Shelterguard™ and Treeguard™ for Shrubs

On exposed sites larger diameters may need two supports.

On sheltered sites two or three internal canes may be sufficient.

The timber stake should be positioned internally when installing SHELTERGUARD and TREGUARD for shrubs which will prevent the guard from pivoting during high winds or if it is knocked.



1

Plant shrub using preferred method and clear surface vegetation within at least 10cm of planting position.




2

Hammer a treated or naturally durable stake, a minimum of 25mm square, into ground about 5cm from tree. If site is exposed, position into the prevailing wind.



3

Place guard over shrub and stake. If necessary, gathering branches together to ensure they are all pointing out the top of the guard.



4

Tighten nylon tie securely around the stake.



Feed tail back through second hole and into the guard to prevent it from being nibbled.



5

Ensure base of guard is flush with ground to provide a safe seal from herbicides and deter animals from burrowing underneath.



6

Your shrub is now safely protected by SHELTERGUARD /TREGUARD for shrubs.



A PGI Company, Fiberweb Geosynthetics Ltd  
Blackwater Trading Estate • The Causeway  
Maldon • CM9 4GG • United Kingdom  
Tel: +44 (0) 1621 874201 • Fax: +44 (0) 1621 874299  
email: [plantcare@tubex.com](mailto:plantcare@tubex.com) • [www.tubex.com](http://www.tubex.com)

 **TUBEX**  
Advancing growth